


# TREA330 Series



VIBRATION ANALYSIS HARDWARE

Premium Miniature Industrial Triaxial Accelerometer, Side Exit 4 Pin Mini-MIL Connector, Follows Cartesian Phase Coordinate System, 100 mV/g, ±5%



## Product Features

Uses J4A, J4C, or J4N Connectors and CB105, CB117, CB119, or CB218 Cables


Cartesian Coordinate Phase Configuration

- ▶ 100 mV/g, ±5% sensitivity tolerance
- ▶ Low Profile Side Exit Case
- ▶ High Frequency Response

### TREA330

4 Pin Connector

Connector Pin	Polarity
A (Axis Y)	(+) Signal/Power
B (Axis X)	(+) Signal/Power
C (Axis Z)	(+) Signal/Power
D	(-) Common/Grid



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TREA330	TREA340	<b>Environmental</b>		
Sensitivity (±5%)		100 mV/g	Temperature Range	-65 to 250°F	-54 to 121°C
Frequency Response (±3dB)	30-900,000 CPM	0.5 Hz-15 kHz	Maximum Shock Protection		10,000 g, peak
Frequency Response (±10%)	60-480,000 CPM	1 Hz-8 kHz	Electromagnetic Sensitivity		CE
Frequency Response (±5%)	480-330,000 CPM	8 Hz-5.5 kHz	Sealing		Welded, Hermetic
Dynamic Range		±50g, peak	<b>Physical</b>		
<b>Electrical</b>			Sensing Element		PZT Ceramic
Settling Time		<2.5 Seconds	Sensing Structure		Shear Mode
Voltage Source (IEPE)		18-30 VDC	Weight	3.9 oz	110 grams
Constant Current Excitation		2-10 mA	Case Material		316L Stainless Steel
Spectral Noise @ 10 Hz		30 µg/√Hz	Mounting		1/4-28
Spectral Noise @ 100 Hz		4 µg/√Hz	Connector (Non-Integral)		4 Pin
Spectral Noise @ 1000 Hz		2 µg/√Hz	Resonant Frequency	2,640,000 CPM	44 kHz
Output Impedance		<100 ohm	Mounting Torque	1 to 2 ft. lbs.	1,4 to 2,7 Nm
Bias Output Voltage		10-14 VDC	Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
Case Isolation		>10 <sup>8</sup> ohm	Calibration Certificate		CA10

## Typical Frequency Response

