

BSFA333-IV Series

Inverse Voltage Biaxial Accelerometer, Side Exit 3 Pin Connector, 100 mV/g, with X and Z Axis, ±15%



VIBRATION ANALYSIS HARDWARE




Product Features

Inverse Voltage Biaxial Accelerometer

- ▶ For Use With Baker Hughes/Commtest Systems
- ▶ Monitors Radially and Axially Simultaneously
- ▶ Compatible with C509 and C519 connectors

BSFA333-IV


4 Pin Connector



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	BSFA333-IV	BSFA343-IV	Environmental		
Sensitivity (±15%)		100 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	60-390,000 CPM	1,0-6500 Hz	Electromagnetic Sensitivity		CE
Dynamic Range		± 50 g, peak	Sealing		Welded, Hermetic
Electrical			Submersible Depth	200 ft.	60 m
Settling Time	<2.5 seconds		Physical		
Voltage Source (IEPE)	-18 to -30 VDC		Sensing Element		PZT Ceramic
Constant Current Excitation	2-10 mA		Sensing Structure		Shear Mode
Spectral Noise @ 10 Hz	27 µg/√Hz		Weight	6.9 oz	195 grams
Spectral Noise @ 100 Hz	6.5 µg/√Hz		Case Material		316L Stainless Steel
Spectral Noise @ 1000 Hz	2.5 µg/√Hz		Mounting		1/4-28
Output Impedance	<100 ohm		Connector (Non-Integral)		3 Pin
Bias Output Voltage	-10 to -14 VDC		Mounting Torque	1 to 2 ft. lbs.	1,4 to 2,7 Nm
Case Isolation	>10 ⁸ ohm		Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate		CA10

Typical Frequency Response



T : 150 210 98804

www.ctc-sensor.com